

Compact Hydraulic Unit E-2012A(x) eco+



Applicable model

- Hydraulic Compact Wire Saw DSM series
- Hydraulic Core Drill SPU series
- Hydraulic Wall Cutter CHW series

Specifications		
Model name	E-2012A eco+	E-2012Ax eco+
Power source	Three phase 200/230V 50/60Hz	Three phase 400V 50/60Hz
Motor	Water-cooled 20kW 2P	
Max. pressure	28MPa	
Discharge	50Hz	23.5-54.5 litter/min
	60Hz	28.3-65.6 litter/min
Oil Tank Capacity	20 litter	
Size (WxLxH)	680x943x902~1,242mm	
Weight	240kg	

Coring

Core Drill (Rig type)

Auto Feed EHAC

Core Drill Options

Diamond Core Bit

Dry Hand Core Drill

Hydraulic Unit E-1524A(x)



Applicable model

- Hydraulic Compact Wire Saw DSM series
- Hydraulic Core Drill SPU series
- Hydraulic Wall Cutter CHW series

Specifications		
Model name	E-1524A	E-1524Ax
Power source	Three phase 200/230V 50/60Hz	Three phase 400V 50/60Hz
Motor	15kW	
Max. pressure	21MPa	
Discharge	50Hz	23.6-43.1 litter/min
	60Hz	28.2-51.7 litter/min
Oil Tank Capacity	60 litter	
Size (WxLxH)	670x1,090x874mm	
Weight	350kg	

Hydraulic Unit E-1124A(x)



Applicable model

- Hydraulic Compact Wire Saw DSM series
- Hydraulic Core Drill SPU series
- Hydraulic Wall Cutter CHW series

Specifications		
Model name	E-1124A	E-1124Ax
Power source	Three phase 200/230V 50/60Hz	Three phase 400V 50/60Hz
Motor	11kW	
Max. pressure	21MPa	
Discharge	50Hz	23.6-43.1 litter/min
	60Hz	28.2-51.7 litter/min
Oil Tank Capacity	60 litter	
Size (WxLxH)	670x1,090x874mm	
Weight	330kg	

Cutting

Wall Cutter

Plunge Cutter

Options for Hydraulic Unit

<p>Hydraulic Hose Assy. Nitto Coupling 20m 5/8</p> <p>Possible to use for extension</p>	<p>Conversion Adaptor B male - F male 1/2</p> <p>Use for conversion Bridgestone coupling and Nitto flat face coupling</p>	<p>Conversion Adaptor B female - F female 1/2</p> <p>Use for conversion Bridgestone coupling and Nitto flat face coupling</p>	<p>Depressurization Tool for Hydraulic Hose</p> <p>Open the coupling to relieve pressure</p>
---	---	---	--

Wire Saw

Hydraulic Unit